


# Schlauchklemmen aus Temperguss, verzinkt Zinc-plated, malleable iron hose clamps




**Schlauchklemmen 2-teilig**

mit angegossenen Zungen  
PN 16 bar

**Two part hose clamps**  
with casted tongues  
PN 16 bar - 227 psi

Art.-Nr. Item No.	SLW Hose I.D.	Spannbereich Range	b mm	St.Gew. Pc.weight	Verp.Einh. Pkg.quan.
1352	13 mm 1/2"	17 - 22 mm	61	91 g	10
1353	19 mm 3/4"	25 - 32 mm	70	97 g	10




**Schlauchklemmen 2-teilig  
DIN 20039 A**

mit losen Zungen  
PN 16 bar

**Two part hose clamps  
DIN 20039 A**  
with separate tongues  
PN 16 bar - 227 psi

Art.-Nr. Item No.	SLW Hose I.D.	Spannbereich Range	b mm	St.Gew. Pc.weight	Verp.Einh. Pkg.quan.
1302	13 mm 1/2"	20 - 29 mm	61,5	124 g	10
1303	19 mm 3/4"	28 - 34 mm	71	122 g	10
1304	25 mm 1"	32 - 40 mm	81	185 g	10
1305	32 mm 1 1/4"	39 - 49 mm	92,5	221 g	10
1306	38 mm 1 1/2"	48 - 60 mm	105	276 g	10
1307	50 mm 2"	60 - 76 mm	115	314 g	10
1308	63 mm 2 1/2"	77 - 94 mm	150,5	605 g	10
1309	75 mm 3"	94 - 115 mm	163	581 g	10
1310	89 mm 3 1/2"	115 - 145 mm	198	1027 g	10




**Schlauchklemmen 2-teilig  
mit Sicherungsklauen  
DIN 20039 B**

mit losen Zungen  
PN 25 bar

**Two part hose clamps  
DIN 20039 B  
with safety claws**  
and separate tongues  
PN 25 bar - 355 psi

Art.-Nr. Item No.	SLW Hose I.D.	Spannbereich Range	b mm	St.Gew. Pc.weight	Verp.Einh. Pkg.quan.
1322	13 mm 1/2"	22 - 29 mm	63	130 g	10
1323	19 mm 3/4"	28 - 33 mm	70	138 g	10
1324	25 mm 1"	35 - 42 mm	84	236 g	10
1325	28 mm 1 7/64"	40 - 47 mm	92	243 g	10
1326	35 mm 1 3/8"	48 - 60 mm	106	301 g	10
1327	42 mm 1 5/8"	53 - 68 mm	117	403 g	10
1328	50 mm 2"	58 - 76 mm	117	391 g	10
1329	65 mm 2 1/2"	75 - 88 mm	154	717 g	10




**Schlauchklemmen 3-teilig  
mit Sicherungsklauen  
DIN 20039 B**

mit losen Zungen  
PN 25 bar

**Three part hose clamps  
DIN 20039 B  
with safety claws**  
and separate tongues  
PN 25 bar - 355 psi

Art.-Nr. Item No.	SLW Hose I.D.	Spannbereich Range	b mm	St.Gew. Pc.weight	Verp.Einh. Pkg.quan.
1330	75 mm 3"	90 - 110 mm	160	717 g	1
1331	105 mm 4"	110 - 135 mm	170	1212 g	1
1333	150 mm 6"	170 - 190 mm	230	2220 g	1



**US - Schlauchklemmen 2-teilig  
mit Sicherungsklauen**

**Two part US - hose clamps  
with safety claws**

Art.-Nr. Item No.	SLW Hose I.D.	Spannbereich Range	b mm	St.Gew. Pc.weight	Verp.Einh. Pkg.quan.
1401	13 mm 1/2"	21 - 27 mm	54	138 g	10
1402	19 mm 3/4"	30 - 35 mm	63	257 g	10
1403	25 mm 1"	36 - 45 mm	83	366 g	10

# Schlauchschellen mit Schneckenantrieb DIN 3017 / W1, Stahl, verzinkt Zinc-plated, steel hose clips with worm-gear, DIN 3017 / W1

Art.-Nr. Item No.	Spannbereich Range	Bandbreite Strap width	St.Gew. Pc.weight	Verp.Einh. Pkg.quan.
4001	8 - 12 mm	9 mm	10 g	100
4002	10 - 16 mm	9 mm	10 g	100
4003	12 - 20 mm	9 mm	12 g	100
4004	16 - 25 mm	9 mm	12 g	100
4005	20 - 32 mm	9 mm	13 g	100
4006	25 - 40 mm	9 mm	14 g	100
4007	32 - 50 mm	9 mm	22 g	50
4008	40 - 60 mm	9 mm	24 g	50
4009	50 - 70 mm	9 mm	27 g	50

## Schlauchschellen mit Schneckenantrieb

**"IDEAL"**

Sechskantkopfschraube mit Kreuzschlitz

## Hose clips with worm-gear

**"IDEAL"**

Bolt with cross-slot hex head



Art.-Nr. Item No.	Spannbereich Range	Bandbreite Strap width	St.Gew. Pc.weight	Verp.Einh. Pkg.quan.
4049	12 - 20 mm	12 mm	16 g	100
4050	16 - 25 mm	12 mm	21 g	100
4051	20 - 32 mm	12 mm	22 g	100
4052	25 - 40 mm	12 mm	24 g	100
4053	32 - 50 mm	12 mm	29 g	50
4054	40 - 60 mm	12 mm	37 g	50
4055	50 - 70 mm	12 mm	40 g	50
4056	60 - 80 mm	12 mm	42 g	50

## Schlauchschellen mit Schneckenantrieb

**"IDEAL"**

Sechskantkopfschraube mit Kreuzschlitz

## Hose clips with worm-gear

**"IDEAL"**

Bolt with cross-slot hex head



Art.-Nr. Item No.	Spannbereich Range	Bandbreite Strap width	St.Gew. Pc.weight	Verp.Einh. Pkg.quan.
4011	8 - 16 mm	9 mm	13 g	100
4012	10 - 16 mm	9 mm	13 g	100
4013	12 - 22 mm	9 mm	14 g	100
4014	16 - 27 mm	9 mm	17 g	100
4015	20 - 32 mm	9 mm	17 g	100
4016	25 - 40 mm	9 mm	19 g	100
4017	35 - 50 mm	9 mm	21 g	100
4018	40 - 60 mm	9 mm	22 g	50
4019	50 - 70 mm	9 mm	21 g	50
4020	70 - 90 mm	9 mm	28 g	25

## Schlauchschellen mit Schneckenantrieb

Sechskantkopfschraube mit Kreuzschlitz

## Hose clips with worm-gear

Bolt with cross-slot hex head



Art.-Nr. Item No.	Spannbereich Range	Bandbreite Strap width	St.Gew. Pc.weight	Verp.Einh. Pkg.quan.
4069	12 - 22 mm	12 mm	16 g	100
4070	16 - 27 mm	12 mm	20 g	100
4071	20 - 32 mm	12 mm	21 g	100
4072	25 - 40 mm	12 mm	23 g	100
4073	35 - 50 mm	12 mm	25 g	100
4074	40 - 60 mm	12 mm	27 g	50
4075	50 - 70 mm	12 mm	29 g	50
4076	60 - 80 mm	12 mm	32 g	50

## Schlauchschellen mit Schneckenantrieb

Sechskantkopfschraube mit Kreuzschlitz

## Hose clips with worm-gear

Bolt with cross-slot hex head

